

# HIGH TEMPERATURE CLIP SILICON

Temp. - 60° C to + 300° C



## Structure:

Light weight and very flexible Silicone ducting

## Material:

Silicone coated glass fabric, silver-grey

## Properties

Good temperature resistance, outer wear strip, flame retardant wall, excellent axial compressibility, good UV and ozone resistance, highly flexible

## Application







Suction of hot fumes, gases or dust in all fields of industry

## Temperature Resistance:

- 60° C to + 300° C

## Standard Length:

3 to 10 meters

					
int mm	kg/m	mm	mm	bar	bar
50	0.40	0.4	30	0.85	0.32
60	0.50	0.4	36	0.68	0.22
76	0.60	0.4	45	0.47	0.14
80	0.62	0.4	48	0.43	0.13
102	0.65	0.4	60	0.3	0.08
110	0.70	0.4	66	0.25	0.07
120	0.72	0.4	72	0.22	0.06
127	0.80	0.4	75	0.21	0.05
152	0.90	0.4	90	0.16	0.04
160	0.94	0.4	96	0.14	0.03
180	1.00	0.4	108	0.12	0.02
203	1.21	0.4	120	0.1	0.02
254	1.70	0.4	175	0.07	0.01
305	2.13	0.4	210	0.05	0.01
350	2.50	0.4	245	0.04	0.01
407	3.10	0.4	280	0.03	0.01
508	4.15	0.4	400	0.02	0.01