


PU HOSE - HEAVY DUTY Ether Grade



K1Z - MSC - PU Hose - Virgin Food Grade



Structure:

Polyether - Polyurethane - Wall thick. 0.8 mm

Characteristics:

Very smooth bore, good abrasion resistance, resistant to oil and petrol, non toxic, free of halogen and softeners, resistant to hydrolysis and microbes

Applications:

Suction and conveying of abrasive particles and granules






Temperature range:

-40°C to + 90°C (short-term up to + 125°C)

Colour:

Transparent



				
int mm	mm	mm	bar	bar
25	0.8	25	1.33	0.38
30	0.8	30	1.24	0.33
40	0.8	40	0.86	0.19
50	0.8	50	0.86	0.19
60	0.8	60	0.76	0.18
70	0.8	70	0.76	0.18
75	0.8	75	0.57	0.17
80	0.8	80	0.57	0.17
90	0.8	90	0.48	0.14
100	0.8	100	0.48	0.14
110	0.8	110	0.38	0.09
120	0.8	120	0.36	0.09
125	0.8	125	0.33	0.07
140	0.8	140	0.29	0.07
150	0.8	150	0.24	0.07
160	0.8	160	0.19	0.04
175	0.8	175	0.19	0.03
180	0.8	180	0.19	0.03
200	0.8	200	0.14	0.02
225	0.8	225	0.14	0.02
250	0.8	250	0.09	0.01
300	0.8	300	0.08	0.01
350	0.8	400	0.06	0.01
450	0.8	450	0.05	0.00
500	0.8	500	0.00	0.00

Depending on installation or operating conditions, the vacuum or pressure values may differ from those stated in the table. In doubtful cases, provide a description of the application you have in mind, and we will be pleased to advice you. Alternative sizes and colours, different tolerances etc. can be supplied on request. Technical Data (at 20°C)

Mob: +91-9843810577 | Phone : 0422 - 23 93 253 | 0422 - 23 93 453

Email : flexaflexhoses@be@gmail.com | pipe.agencies@gmail.com

www.flexaflexhoses.in | www.pipeagencies.in +91-94 897 38 415

FLEXAFLEX HOSES INDUSTRIES
51, Dr. NANJAPPA ROAD
COIMBATORE - 641 018